

BEST AVAILABLE COPY

## Listing of Claims.

1. (currently amended)

A clothing hanging device, which includes:

a base having a back side configured for mounting to a vertical support and a front side;

a first retaining member connected to said front side and extending outward therefrom;

a second retaining member disposed adjacent said first retaining member;

first means for biasing said second retaining member toward said first retaining member;

and

first means for simultaneously permitting said biasing means to be compressed with part of one's hand while permitting insertion of an article to be hung between said retaining members with the same hand whereupon at least a portion of the article ~~garment~~ can be supportively retained between and by said retaining members.

2. (currently amended) The clothing hanging device of claim 1, wherein said base is elongated and ~~having a long axis~~ vertically disposed.

3. (original) The clothing hanging device of claim 1, wherein said first retainer member includes a flared end extending outward from said front side.

4. (original) The clothing hanging device of claim 1, wherein said first retaining member is rigid.

5. (original) The clothing hanging device of claim 1, wherein said second retaining member is rigid.

6. (currently amended) The clothing hanging device of claim 1, wherein at least one of said retaining members includes a ridged surface adjacent a point of contact between said retaining

members therebetween.

7. (currently amended) The clothing hanging device of claim 1, wherein said front side is disposed at a predetermined angle with respect to the vertical support when said base is mounted thereto such ~~that~~ than an upper end of said front side is more outwardly disposed from the support than a lower end of said front side.

8. (original) The clothing hanging device of claim 7, wherein said front side is hingedly connected to said back side.

9. (currently amended) The clothing hanging device of claim 8, which includes a latch for latching said ~~front~~ front side to said back side.

10. (withdrawn).

11. (withdrawn).

12. (original) The clothing hanging device of claim 1, wherein said first biasing means includes an angled-spring metal.

13. (withdrawn).

14. (currently amended) The clothing hanging device of claim 1, wherein said device permits removal of the retained article ~~a retained garment~~ by pulling thereon ~~on a free end of the garment~~ with sufficient force to overcome a spring force constant of said biasing means.

15. (original) The clothing hanging device of ~~claim 1, wherein~~ claim 1, wherein one of said retaining members includes said first permitting means.

16. (currently amended) The clothing hanging device of claim 1, which includes a third retaining member connected to said front side and extending outward therefrom and longitudinally spaced from said first retaining member, a fourth retaining member disposed

adjacent said third retaining member, second means for biasing said fourth retaining member toward said third retaining member, and second means for simultaneously permitting said second biasing means to be compressed with part of one's hand while permitting insertion of an article a ~~garment~~ between said third and fourth retaining members with the same hand whereupon the article can be supportively retained between and by said retaining members.

17. (currently amended) The clothing hanging device of claim 16, wherein said base is elongated and ~~having a long axis~~ vertically disposed.

18. (original) The clothing hanging device of claim 17, wherein said first and second retaining members are horizontally disposed with respect to said third and fourth retaining members.

19. (currently amended) The clothing hanging device of claim 17, wherein said first and second retaining members are horizontally ~~staggared~~ staggered with respect to said third and fourth retaining members.

20. (new) The clothing hanging device of claim 1, wherein said permitting means includes an outwardly disposed portion on said second retaining member which is exposed from said first retaining member in a manner to permit access thereto enabling independent actuation of said biasing means by application of force applied to said portion to displace said retaining members without the need of applying force on said first retaining member.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.